HYDROTUR AWGT 46

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE

COMPANY

Product Name HYDROTUR AWGT 46

Manufacturer PETRON CORPORATION

JESUS ST., PANDACAN, MANILA

PHILIPPINES

Product Type Petroleum Hydrocarbons with Additives

Recommended Use Hydraulic Fluid

Telephone No. (632) 8-884-9200

Website www.petron.com

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION Not Classified as Hazardous Substance

GHS LABELING

Pictogram No symbol

Signal Word No signal word

Hazard Statement No hazard statement

Other Hazard Information:

Health Hazards Not expected to be a health hazard when used under normal conditions.

Physical / Chemical Hazards No significant hazards.

Environmental Hazards Not classified as dangerous to the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition	CAS Number	%Weight
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	99.0 – 99.5
Zinc dithiophosphate	4259-15-8	<0.5

In general, the product does not contain components that may be a significant health and safety hazard as long as normal precautions in handling petroleum products are observed and good standards of industrial and personal hygiene are maintained.

SECTION 4:	FIRST AID MEASURES
Eye Contact	Immediately flush eyes with large amount of water for at least 15 minutes or until irritation subsides. If irritation persists, get prompt medical attention.
Skin Contact	Immediately flush with large amount of water; use soap if available. Remove contaminated clothing, including shoes, and launder before reuse.



Inhalation

This product has low vapor pressure and is not expected to present an inhalation problem at ambient temperature. However, if overexposed to oil mist, using proper respiratory protection, immediately remove the affected person immediately to fresh air. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

Ingestion

If swallowed, DO NOT induce vomiting. If individual is conscious, give milk or water to dilute stomach contents. Keep warm and quiet. Get immediate medical attention. DO NOT attempt to give anything by mouth to an unconscious person.

SECTION 5:

FIRE-FIGHTING MEASURES

Flash Point, COC, °C

226

Extinguishing Media

In case of fire use foam, carbon dioxide or dry chemical extinguishers.

Special Fire-fighting Procedures

Water jets should not be used directly on igniting products. Avoid spraying water directly into storage containers due to danger of over-boil. However, water may be used to cool exposed containers, structures and equipment adjacent to fire. Respiratory and eye protection required for fire-fighting personnel.

Decomposition Products Under Fire Conditions

Fumes, smoke, oxides of sulfur, nitrogen, carbon and other toxic gases

may be formed.

SECTION 6:

ACCIDENTAL RELEASE MEASURES

Land Spill

Taking normal safety precaution, eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills, implement cleanup procedures. For large spills, implement clean-up procedures and, if in public area, keep public away and advise authorities. Prevent liquid from entering sewers, water courses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with a suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Water Spill

Use booms to confine spills immediately. Remove from water surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

SECTION 7:

HANDLING AND STORAGE

Handling Procedures

Keep away from potential sources of ignition. Open container in a well-ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Wash thoroughly after handling. "Empty" containers with retained product residue (liquid or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause death or injury. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed off.

Storage Procedures

Do not store near potential sources of ignition. Store in a well-ventilated area. Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 60°C for extended periods of time or if heat sources in excess of 70°C are used.



SECTION 8:

EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Controls

The following are the exposure limits for the major components of this product (when mists/aerosol may occur).

Component	CAS-No.	Source	Value
Distillates (petroleum), hydrotreated heavy	64742-54-7	ACGIH	Not available
paraffinic			

Personal Protection

Ventilation Procedures The use of local exhaust ventilation is recommended to control mists or

vapors. Additional ventilation or exhaust may be required to maintain air

concentrations below exposure limits.

Gloves Protection Use chemical resistant gloves.

Eye Protection Where contact may occur, wear safety glasses with side shields.

vapor and high efficiency filter cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

Clothing Recommendation Wear either a chemical protective suit or apron when potential for contact

with material exists. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel

that could entrap the material and cause a skin reaction.

SECTION 9:

PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear

Odor Characteristic of petroleum products

Kinematic Viscosity at 40°C, cSt 45.60 Kinematic Viscosity at 100°C, cSt 7.180 Density at 15°C, kg/L 0.8587 Flash Point, °C 226 рΗ No data Boiling Point, °C No data Melting Point, °C No data Vapor Pressure, kPa No data No data Vapor Density Insoluble Solubility in Water **Evaporation Rate** No data

Flammability Not flammable

Partition Coefficient No data
Auto-ignition Temperature, C No data
Decomposition Temperature, C No data
Explosion limits No data



SECTION 10: STABILITY AND REACTIVITY Stability This product is stable under recommended storage and handling conditions. Incompatibility Not available **Polymerization** Not Applicable **TOXICOLOGICAL INFORMATION SECTION 11:** Information given is based on data on the components and the toxicology of **Basis for Assessment:** similar products. **Acute Toxicity** Distillates (Petroleum) Hydrotreated heavy Oral, LD50 >5000 mg/kg (Rat) paraffinic Dermal, LD50 >2000 mg/kg (Rat) Inhalation, Mist LC50 2.18 mg/L 4hr (Rat) Zinc Dithiophosphate Oral, LD50 3100 mg/kg (Rat) Dermal, LD50 >5000 mg/kg (Rabbit) Inhalation, Mist LC50 None Not classified to be an inhalation hazard under normal conditions of use. **Acute Inhalation Toxicity** Skin Corrosion/Irritation Low order of toxicity. Frequent or prolonged contact may cause mild skin discomfort. Serious Eye Damage/Irritation Slight irritation might occur. Respiratory/Skin Sensitization There was no evidence of skin sensitization when the product was applied to human skin. No available information **Germ Cell Mutagenicity Aspiration Hazard** Minimal toxicity Carcinogenicity EU classification of carcinogenicity of petroleum distillates used does not apply since product does not contain DMSO extract beyond 3% according to INCHEM. **Reproductive Toxicity** No available information **ECOLOGICAL INFORMATION SECTION 12:**

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity

Distillates (petroleum) hydrotreated heavy paraffinic

Fish (LC50/96-hours) >5000 mg/L (Oncorhynchus)
Crustaceans (EC50/48-hours) 1,000 mg/L (Daphnia magna)
Algae (EC50/96-hours) >1000 mg/L (Scenedesmus)

Environmental Mobility Oil component of this product floats and can migrate from water to land.



Environmental Degradability	Data have not been determined specifically for this product, but it is not expected that it will be "readily" biodegradable.
Ecotoxicity & Bioaccumulation	Data have not been determined specifically for this product, but it is not expected to be harmful to aquatic organisms.
	DIODOG A GOVERNO DE CARGO DE C
SECTION 13:	DISPOSAL CONSIDERATIONS
Waste Disposal	Material, if discarded, is expected to be hazardous waste due to toxicity. Waste management should be in compliance with local and national regulations.
Local Legislation	Disposal should be in accordance with applicable regional, national and local laws and regulations.
SECTION 14:	TRANSPORT INFORMATION
Air	(ICAO/IATA). This product is not regulated for air transport.
Land	This product is not regulated for road/rail transport.
Sea	IMDG (Packaged Goods and BLCs). This product is not regulated for sea transport
SECTION 15:	REGULATORY INFORMATION

Material is non-hazardous chemical under Occupational Safety and Health (Classification, Labeling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

The Chemical Substances present in this product are listed under Philippine Inventory of Chemicals and Chemical Substance (PICCS).

SECTION 16:	OTHER INFORMATION
Approvals	Research and Development Department Petron Corporation
This safety data sheet contains the following	lowing revisions 1

This is a computer-generated form and does not require a signature.

The information and recommendations contained herein are based on the data sheet and sources believed to be accurate and correct and Petron makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations contained in the SDS. It is your responsibility to contact Petron to ensure that this document is the most current available from Petron. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use and to ensure the safe handling and use of the product. If the user repackages this product, it is the user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Petron accepts no responsibility and hereby disclaim all liability for any harmful effects which may be caused by purchase, resale, use, exposure or disposal of the product. Users must comply with all local laws and regulations. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "Petron" is used for convenience, and may include any one or more of Petron Corporation, Petron Oil & Gas International Sdn Bhd or any affiliates in which they directly or indirectly hold any interest. In no event, shall Petron or its suppliers be liable for any direct or indirect loss of profits or for any other special, indirect or consequential damages, nor shall the liability of Petron on any claim for damages arising out of or connected with the sale, delivery or use of the product purchased exceed the purchase price of the product.

