

PETRON REV-X HD4X

DESCRIPTION

PETRON Rev-X HD4X with DC Technology is a high performance multi-grade engine oil designed to provide ultimate protection to heavy-duty diesel vehicles requiring an API CF quality level.

Formulated with DC Technology additive system and also boosted with four times performance additives to protect the engines to stubborn deposits, wear, sludge, and copper-bearing corrosion.

PROPERTIES

- It provides optimal defense against acid attack and corrosion when subjected to high temperature and engine stress.
- It gives first-rate protection against formation of gums and varnish due to its high oxidation and thermal stability.
- It provides exceptional wear protection on critically loaded components for longer engine life.

GRADE

- SAE 15W-40

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C	0.8795
Flash Point, COC, °C	226
Color, ASTM	2.0
Kinematic Viscosity at 40°C, cSt	103.2
Kinematic Viscosity at 100°C, cSt	14.06
Viscosity Index	138
TBN, mg KOH/g	7.5

APPLICATIONS

- Diesel-fed vehicles requiring an API CF quality.
- Mixed fleets of automotive diesel vehicles such as FX, trucks, and busses.
- Off-road vehicles, agricultural tractors, and equipment.

QUALITY LEVELS

It meets the requirements of:

- API CF/SF
- ACEA E1-96
- MB-Approval 227.1