



# PETRON ATF PREMIUM HTP

## DESCRIPTION

Petron ATF Premium HTP is a premium grade, high performance automatic transmission fluid formulated to provide excellent resistance to oxidation even under high temperature and severe operating condition.

## PROPERTIES

- Provides excellent resistance to oxidation from exposure to high temperature.
- Provides extended protection in friction stability and clutch durability
- Protects gears, bearings, clutch plates, seals, and other components from wear and corrosion.
- Excellent foaming characteristics for optimum operability and longer transmission life.

## GRADE

SAE 20

## APPLICATION

- Suitable for use in most light duty planetary gear service fill applications.
- Suitable for use for
  - General Motor's Dexron IIIH
  - Mercon V, Honda Z-1, Hyundai/Kia Red 1-K, SP-II, SP-III
  - Isuzu ATF II, III
  - Mazda F-1, M-III, Type T-IV
  - Mitsubishi SP-II, SP-III
  - Nissan Matic D, J, K, W
  - Subaru HP
  - Suzuki 3314, 3317
  - Toyota / Lexus D-II, T, T-III, T-IV
  - Allison C-4
  - ATF Specifications from the following OEMs: Audi, BMW, Chrysler, Daimler, Dodge, Jaguar, Jeep, Land Rover, MAN, Maserati, Mercedes-Benz, Mini, Porsche, Volkswagen, and Volvo

## QUALITY LEVELS

JASO IA

## TYPICAL CHARACTERISTICS

Density at 15.6°C, kg/li	0.8505
Flash Point, COC, °C	218
Color, ASTM	Red
Kinematic Viscosity at 40°C, cSt	35.72
Kinematic Viscosity at 100°C, cSt	6.743
Viscosity Index	149
TBN (mg KOH/g)	3.6