

PETRON SPRINT 4T SCOOTER OIL SYNTHETIC BLEND

DESCRIPTION

PETRON SPRINT 4T SCOOTER OIL Synthetic Blend with TCS is a premium performance motorcycle oil formulated to provide superior protection operating in severe service and extreme driving condition.

Formulated with Thermal Control System (TCS) additive technology, friction modifier, and synthetic blend baseoils, it will deliver the ultimate protection needed for automatic motorbikes and scooters operating on stop-go traffic and variable weather conditions.

PROPERTIES

- Excellent wear protection for longer engine life.
- Excellent shear stability to resist oil thinning and breakdown when subjected to engine stress during variable-temperature operation.
- It prevents and removes sludge and deposits for excellent engine cleanliness.
- It reduces noise and vibration for smooth engine drive and acceleration.

GRADE

- SAE 10W-40

APPLICATIONS

- Four-stroke motorcycle engines with automatic transmission
- Scooters

QUALITY LEVEL

- API SL
- JASO MB

TYPICAL CHARACTERISTICS

Specific Gravity at 15.6 °C	0.8655
Flash Point, COC, °C	242
Color, ASTM	L 2.0
Kinematic Viscosity at 40°C, cSt	103.3
Kinematic Viscosity at 100°C, cSt	14.54
Viscosity Index	145