



PETRON REV-X TURBO HTP

DESCRIPTION

PETRON REV-X TURBO HTP is a high premium, PAO-based fully synthetic 5W-40 engine oil recommended for naturally aspirated and turbocharged four-stroke diesel engines. It is specially designed to provide excellent engine performance of today's high performance vehicles.

PROPERTIES

- Prevents soot and piston deposits to maintain superior engine cleanliness and efficiency.
- Gives excellent protection against wear and corrosion for longer engine life.
- Provides extended engine protection due to its outstanding thermal and oxidation resistance.
- Prolongs the life of emission control systems such as diesel particulate filters (DPF) and exhaust gas recirculation (EGR).

GRADE

SAE 5W-40

APPLICATION

- Turbocharged or supercharged high performance heavy duty diesel engines under both low speed-high speed and high speed-high load conditions.
- Light duty trucks
- Gasoline engines requiring an API SN lubricating performance

QUALITY LEVELS

- It is approved and licensed according to the specifications of:
 - MAN 3575
 - Cummins CES 20081
 - Mercedes-Benz Approval 228.31
 - Volvo VDS-4
 - Mack EO-O Premium Plus
 - Renault VI RLD-3
- It meets the requirements of:
 - API CJ-4/SN
 - ACEA E9-12

TYPICAL CHARACTERISTICS

Density at 15.6°C, kg/li	0.8531
Flash Point, COC, °C	200
Color, ASTM	L2.5
Kinematic Viscosity at 40°C, cSt	91.44
Kinematic Viscosity at 100°C, cSt	14.30
Viscosity Index	162
TBN (mg KOH/g)	10.0