# **STM 40**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE

**COMPANY** 

Product Name STM 40

Manufacturer PETRON CORPORATION

JESUS ST., PANDACAN, MANILA

**PHILIPPINES** 

Product Type Petroleum Hydrocarbons with Additives

Recommended Use Non-critical gasoline engine applications

Telephone No. (02) 8-884-9200

Website www.petron.com

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION Not Classified as Hazardous Substance

**GHS LABELING** 

Pictogram No symbol

Signal Word No signal word

Hazard Statement No hazard statement

Other Hazard Information:

Health Hazards Not expected to be a health hazard when used under normal conditions.

Physical / Chemical Hazards No significant hazards.

Environmental Hazards Not classified as dangerous to the environment.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition	CAS Number	%Weight
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	70.0 – 80.0
Highly refined mineral oil	64742-62-7	20.0 - 30.0

SECTION 4:	FIRST AID MEASURES
SECTION 4:	FIRST AID MEASUR

**Eye Contact** Immediately flush eyes with large amount of water for at least 15 minutes or

until irritation subsides. If irritation persists, get prompt medical attention.

Skin Contact Immediately flush with large amount of water; use soap if available. Remove

contaminated clothing, including shoes, and launder before reuse.

**Inhalation**This product has low vapor pressure and is not expected to present an inhalation problem at ambient temperature. However, if overexposed to oil

mist, using proper respiratory protection, immediately remove the affected



person immediately to fresh air. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

# Ingestion

If swallowed, DO NOT induce vomiting. If individual is conscious, give milk or water to dilute stomach contents. Keep warm and quiet. Get immediate medical attention. DO NOT attempt to give anything by mouth to an unconscious person.

SECTION 5:	FIRE-FIGHTING MEASURES
------------	------------------------

Flash Point, COC, °C 232

**Extinguishing Media** In case of fire use foam, carbon dioxide or dry chemical extinguishers.

**Special Fire-fighting Procedures** 

Water jets should not be used directly on igniting products. Avoid spraying water directly into storage containers due to danger of over-boil. However, water may be used to cool exposed containers, structures and equipment adjacent to fire. Respiratory and eye protection required for fire-fighting personnel.

**Decomposition Products Under Fire Conditions** 

Fumes, smoke, oxides of sulfur, nitrogen, carbon and other toxic gases may be formed.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **Land Spill**

Taking normal safety precaution, eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills, implement cleanup procedures. For large spills, implement clean-up procedures and, if in public area, keep public away and advise authorities. Prevent liquid from entering sewers, water courses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with a suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

### Water Spill

Use booms to confine spills immediately. Remove from water surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

# SECTION 7: HANDLING AND STORAGE

#### **Handling Procedures**

Keep away from potential sources of ignition. Open container in a well-ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Wash thoroughly after handling. "Empty" containers with retained product residue (liquid or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause death or injury. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed off.

#### **Storage Procedures**

Do not store near potential sources of ignition. Store in a well-ventilated area. Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 60°C for extended periods of time or if heat sources in excess of 70°C are used.

#### SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

# **Exposure Controls**



Rev 6 10/2020 Issue Date: 10/2020 Page 2 of 5 The following are the exposure limits for the major components of this product (when mists/aerosol may occur).

Component	CAS-No.	Source	Value
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	ACGIH	Not available
Highly refined mineral oil	64742-62-7	ACGIH	5 mg/m <sup>3</sup>
		SG OEL	5 mg/m <sup>3</sup>
		SG OEL	10mg/m <sup>3</sup>

#### **Personal Protection**

Ventilation Procedures The use of local exhaust ventilation is recommended to control mists or

vapors. Additional ventilation or exhaust may be required to maintain air

concentrations below exposure limits.

Gloves Protection Use chemical resistant gloves.

Eye Protection Where contact may occur, wear safety glasses with side shields.

Respiratory Protection Use NIOSH/OSHA approved full-face respirator with a combination organic

> vapor and high efficiency filter cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

Clothing Recommendation Wear either a chemical protective suit or apron when potential for contact

with material exists. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel

that could entrap the material and cause a skin reaction.

# SECTION 9:

# PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear

Kinematic Viscosity at 40°C, cSt

Odor Characteristic of petroleum products

145.1

Kinematic Viscosity at 100°C, cSt 14.80 Density at 15°C, kg/L 0.8867 Flash Point, °C 232 No data pН Boiling Point, °C No data Melting Point, °C No data Vapor Pressure, kPa No data Vapor Density No data Solubility in Water Insoluble No data **Evaporation Rate** Flammability Not flammable

No data **Partition Coefficient** Auto-ignition Temperature, C No data Decomposition Temperature, C No data



Issue Date: 10/2020 Page 3 of 5 Explosion limits No data

SECTION 10:	STABILITY AND REACTIVITY	
Stability	This product is stable under recommended storage and handling conditions.	
Incompatibility	Not available	
Polymerization	Not Applicable	
SECTION 11:	TOXICOLOGICAL INFORMA	ATION
Basis for Assessment:	Information given is based on similar products.	data on the components and the toxicology of
Acute Toxicity Distillates (Petroleum)		
Hydrotreated heavy paraffinic	Oral, LD50 Dermal, LD50 Inhalation, Mist LC50	>15000 mg/kg (Rat) >5000 mg/kg (Rabbit) 2.18 mg/L 4hr (Rat)
Highly refined mineral oil	Oral, LD50 Dermal, LD50 Inhalation, LC50	>5000 mg/kg (Rat) >5000 mg/kg (Rabbit) >5 mg/l (Rat)
Acute Inhalation Toxicity	Not classified to be an inhalat	ion hazard under normal conditions of use.
Skin Corrosion/Irritation	Low order of toxicity. Frequ discomfort.	ent or prolonged contact may cause mild skin
Serious Eye Damage/Irritation	Slight irritation might occur.	
Respiratory/Skin Sensitization	There was no evidence of skin sensitization when the product was applied to human skin.	
Germ Cell Mutagenicity	No available information	
Aspiration Hazard	Minimal toxicity	
Carcinogenicity		nicity of petroleum distillates used does not contain DMSO extract beyond 3% according to
Reproductive Toxicity	No available information	
SECTION 12:	ECOLOGICAL INFORMATION	DN

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

# **Acute Toxicity**

Distillates (petroleum) hydrotreated heavy paraffinic

Fish (LC50/96-hours) >5000 mg/L (Oncorhynchus) Crustaceans (EC50/48-hours) 1,000 mg/L (Daphnia magna) >1000 mg/L (Scenedesmus)



<b>Environmental Mobility</b>	Oil component of this product floats and can migrate from water to land.
Environmental Degradability	Data have not been determined specifically for this product, but it is not expected that it will be "readily" biodegradable.
Ecotoxicity & Bioaccumulation	Data have not been determined specifically for this product, but it is not expected to be harmful to aquatic organisms.
SECTION 13:	DISPOSAL CONSIDERATIONS
Waste Disposal	Material, if discarded, is expected to be hazardous waste due to toxicity. Waste management should be in compliance with local and national regulations.
Local Legislation	Disposal should be in accordance with applicable regional, national and local laws and regulations.
SECTION 14:	TRANSPORT INFORMATION
Air	(ICAO/IATA). This product is not regulated for air transport.
Land	This product is not regulated for road/rail transport.
Sea	IMDG (Packaged Goods and BLCs). This product is not regulated for sea transport
SECTION 15:	REGULATORY INFORMATION

Material is non-hazardous chemical under Occupational Safety and Health (Classification, Labeling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

The Chemical Substances present in this product are listed under Philippine Inventory of Chemicals and Chemical Substance (PICCS).

SECTION 16:	OTHER INFORMATION
Approvals	Research and Development Department Petron Corporation
This safety data sheet contains the following	llowing revisions 7

This is a computer-generated form and does not require a signature.

The information and recommendations contained herein are based on the data sheet and sources believed to be accurate and correct and Petron makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations contained in the SDS. It is your responsibility to contact Petron to ensure that this document is the most current available from Petron. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use and to ensure the safe handling and use of the product. If the user repackages this product, it is the user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Petron accepts no responsibility and hereby disclaim all liability for any harmful effects which may be caused by purchase, resale, use, exposure or disposal of the product. Users must comply with all local laws and regulations. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "Petron" is used for convenience, and may include any one or more of Petron Corporation, Petron Oil & Gas International Sdn Bhd or any affiliates in which they directly or indirectly hold any interest. In no event, shall Petron or its suppliers be liable for any direct or indirect loss of profits or for any other special, indirect or consequential damages, nor shall the liability of Petron on any claim for damages arising out of or connected with the sale, delivery or use of the product purchased exceed the purchase price of the product.

